

# I-Net™ Networked Access Control Units



**I-Net™ Door Controller**

**I-Net™ Plus Door Controller**

**I-Net™ Supervised Door Controller**

**I-Net™ Reader Expansion Board**

**I-Net™ Input / Output Expansion Board**

Part Number	CS-IDC-100	CS-IDC-200	CS-IDC-300	AC-3151	AC-4311
Web Browser Configuration Interface	YES	YES	YES	NO	NO
TCP/IP	YES	YES	YES	NO	NO
DHCP Support	YES	YES	YES	NO	NO
RS232	NO	YES	YES	NO	NO
USB	NO	YES	YES	NO	NO
RS485	YES	YES	YES	YES	YES
Power Requirements	600mA @ 12 VDC	600mA @ 12 VDC	600mA @ 12 VDC	450mA @ 12 VDC	450mA @ 12 VDC
Maximum Cardholders	100,000	100,000	100,000	N/A	N/A
Maximum Event History Buffer	100,000	100,000	100,000	N/A	N/A
Maximum Schedules	16	16	16	N/A	N/A
Maximum Wiegand or Clock & Data Readers	2	2	2	2	N/A
Maximum RS485 Readers	2 or 16	2 or 16	2 or 16	N/A	N/A
Maximum Additional I-Net Units Connected via RS485	15	15	15	N/A	N/A
Maximum RS485 Slave Devices (AC-1100/2010/3151/4311/Aperio)	16	16	16	N/A	N/A
Maximum Inputs	5	5	5	4	8
Maximum Supervised Inputs	N/A	N/A	6	N/A	N/A
Maximum Outputs	4	4	4	2	8
Dimensions (mm)	170 x 135 x 15	170 x 135 x 15	170 x 135 x 15	100 x 110 x 15	160 x 125 x 15
Warranty	2 Years				