

The AC-1202 from Controlsoft is a Proximity Reader in an industry standard panel mount housing. The AC-1202 connects to an Access Control Unit via an industry standard Wiegand connection.

## **Features and Benefits**

- Proximity Technology (Contactless)
- Electronics Potted for Environmental Protection
- Tri-colour LED and buzzer for user feedback
- Industry Standard Panel Mount Format
- (40mm square aperture)
- Dimensions: 62mm x 62mm x 18mm

## Compatible Cards / Tags

- AC-7080 Clamshell card
- AC-7100 Standard ISO card
- AC-7110 Numbered prox cards
- AC-7101 Keyfob
- AC-7130 ISO Magstripe & Prox card
- AC-7102 Thin Keyfob
- AC-7103 Sticker tag

## Technical

- Housing rated to IP68
- Wiegand 26bit format
- Frequency: 125Khz
- Wiegand Interface
- 12Vdc @ 100mA
- Read Range: up to 40mm
- Operating temperature: -30 °C to +65 °C
- Operating humidity: 0 to 95% non-condensing
- 2 Year Warranty

## Part Number: AC-1202

© 2019 Controlsoft Limited. All rights reserved. Controlsoft and the Controlsoft logo are registered trademarks of Controlsoft Limited in Europe, the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. 9030-0003 September 2019 E&OE