

The AC-3102 from Controlsoft is a standalone Access Control Unit with integral reader in an industry standard panel mount housing, providing cost effective access control for a single door.

Features and Benefits

- Standalone Single Door Solution
- Supports up to 30 Users
- Suitable for Indoor or Outdoor Use
- Programmed with a Master Card (Supplied)
- Tri-colour LED and Buzzer for Ease of Use
- Industry Standard Panel Mount Format
- (40mm square aperture)
- Dimensions: 62mm x 62mm x 18mm

Compatible Cards / Tags

- AC-7080 Clamshell card
- AC-7100 Standard ISO card
- AC-7101 Keyfob
- AC-7130 ISO Magstripe & Prox card
- AC-7102 Thin Keyfob
- AC-7103 Sticker tag

Part Number: AC-3102

Technical

- Housing rated to IP68
- 1 x Input for a Request to Exit Button
- 1 x Relay Output for Lock
- Pulse or Latch Relay Mode
- Frequency: 125KHz
- 12-16Vdc @ 100mA
- Operating temperature: -20 °C to +60 °C
- Operating humidity: 0 to 95% non-condensing
- 2 Year Warranty

© 2019 Controlsoft Limited. All rights reserved. Controlsoft and the Controlsoft logo are registered trademarks of Controlsoft Limited in Europe, the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. 9030-0009 September 2019 E&OE