www.controlsoft.com



The AC-3210-V from Controlsoft is a standalone Access Control Unit complete with an AC-3212 vandal resistant reader head, providing cost effective access control for a single door. This kit comes with one reader, however, an additional mullion, vandal resistant or panel mount reader can be purchased to allow for In and Out reader operation.

Features and Benefits

- Standalone Single Door Solution
- Supports up to 999 Users
- Reader Head Suitable for Indoor or Outdoor Use
- Programmed with a Master Card (Supplied)
- Bi-colour LED and Buzzer on Reader Head for Ease of Use
- 3 Digit Display and 2 Internal Push Buttons on Controller
- Optional Second Reader Head can be purchased for Reader In/Out
- Dimensions (Controller): 150mm x 100mm x 30mm
- (Reader Head): 93mm x 93mm x 26mm

Compatible Readers

- AC-3211 Mullion reader
- AC-3212 Vandal resistant reader
- AC-3213 Panel mount reader

Technical

- Reader Head Housing rated to IP68
- 2 x Inputs for Request to Exit and Fire Alarm
- 2 x Relay Outputs for Lock and Siren
- Frequency: 125KHz
- 12-24V ac or dc (100mA @ 12Vdc)
- Operating temperature: -20 °C to +60 °C
- Operating humidity: 0 to 95% non-condensing
- 2 Year Warranty
- Boxed Weight: 1024g

Compatible Cards / Tags

- AC-7080 Clamshell card
- AC-7100 Standard ISO card
- AC-7101 Keyfob
- AC-7130 ISO Magstripe & Prox card
- AC-7102 Thin Keyfob
- AC-7103 Sticker tag

Part Number: AC-3210-V

© 2019 Controlsoft Limited. All rights reserved. Controlsoft and the Controlsoft logo are registered trademarks of Controlsoft Limited in Europe, the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. 9030-0014 September 2019 E&OE